APPENDIX 14G

UNITIZATION PROCEDURES FOR BOXED AMMUNITION AND COMPONENTS ON 4-WAY ENTRY PALLETS


CARTRIDGE, CALIBER .50, PACKED 210 PER WOODEN BOX, UNITIZED 24 BOXES PER 35" X $45\frac{1}{2}$ " PALLET; APPROX BOX SIZE $15\frac{3}{8}$ " L X $9\frac{1}{2}$ " W X $14\frac{7}{8}$ " H

PALLET UNIT DATA							
ITEMS INCLUDED		HAZARD CLASSIFICATION				WEIGHT	
NSN	DODIC	DOT CLASS	CG CLASS	QD CLASS	COMP GROUP	(LBS)	
1305- 00-028-6453	A534	С	I	1.4	G	2, 110	

NOTICE: THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002.

	REVI	SIONS	In H		11/13/15	
	TT/	1	CHECKER (V) IN	1/2	A Light	READINESS COMMAN
			1			10 Fatte
	/		DEGRE - BEC		V J DAGAN - 12	
L			APPROVED BY ORDER OF COMMANDING GENERAL, U.S. ARBY MATERIEL DEVELOPMENT AND READINESS COMMAND (DARCOM)			
		U. S. ARMY DEFENSE ASSUMITION CENTER AND SCHOOL				
			U.S.	ARMY D	ARCOM	DRAWING
			APRIL 1980			
1 1			CLASS	DIVISION	DRAWING	FILE
			10	40	4116/14G	20PA
			19	48	4110/146	1002

DO NOT SCALE



24 BOXES OF .50 CALIBER CARTRIDGES (210 PER BOX) @ 85 LBS --- 2,040 LBS (APPROX)

TOTAL WEIGHT ------2,110 LBS (APPROX)
CUBE ------ 35.8 CU FT (APPROX)

5 189

BILL OF MATERIAL PALLET, 35" X 45-1/2" ------ 1 REQD ------- 65 LBS STEEL STRAPPING, 3/4" ----- 67.42" REQD ------ 4.82 LBS SEAL FOR 3/4" STRAPPING ---- 5 REQD ------- NIL


DUNNAGE ----

GENERAL NOTES

- A. THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-116-20PA 1002. TO PRODUCE AN APPROVED UNIT LOAD, ALL PERTINENT PROCEDURES, SPECIFICATIONS AND CRITERIA SET FORTH WITHIN THE BASIC DRAWING WILL APPLY TO THE PROCEDURES DELINEATED IN THIS APPENDIX. ANY EXCEPTIONS TO THE BASIC PROCEDURES ARE SPECIFIED IN THIS APPENDIX.
- B. DIMENSIONS, CUBE AND WEIGHT OF A PALLET UNIT WILL VARY SLIGHTLY DEPENDING UPON THE ACTUAL DIMENSIONS OF THE BOXES AND THE WEIGHT OF THE SPECIFIC ITEM BEING UNITIZED.
- C, INSTALL EACH HORIZONTAL STRAP TO ENCIRCLE A LAYER OF BOXES ON THE PALLET. HORIZONTAL STRAPS MUST BE TENSIONED AND SEALED PRIOR TO APPLICATION OF TIEDOWN STRAPS.
- D. INSTALL EACH TIEDOWN STRAP TO PASS UNDER THE TOP DECK BOARDS OF THE PALLET AND TO BE LOCATED AS SHOWN. TIEDOWN STRAPS WILL NOT BE APPLIED UNTIL THE HORIZONTAL STRAPS HAVE BEEN TENSIONED AND SEALED.
- E. THE FOLLOWING DARCOM DRAWINGS ARE APPLICABLE FOR OUT-LOADING AND STORAGE OF THE ITEMS COVERED BY THIS APPENDIX,

CARLOADING	DRAWING 19-48-4115-5PA 1002
TRUCKLOADING	DRAWING 19-48-4117-11PA 1003
STORA GE	DRAWING 19-48-4118-1-2-14-22PA 1002

- F. FOR METHOD OF SECURING A STRAP CUTTER TO THE PALLET UNIT, SEE DARCOM DRAWING 19-48-4 127-20 P1000.
- G. IF ITEMS COVERED HEREIN ARE UNITIZED PRIOR TO ISSUANCE OF THIS APPENDIX, THE BOXES NEED NOT BE REUNITIZED SOLELY TO CONFORM TO THIS APPENDIX.
- H. THE UNITIZATION PROCEDURES DEPICTED HEREIN MAY ALSO BE USED FOR UNITIZING .50 CALIBER CARTRIDGES WHEN IDENTIFIED BY DIFFERENT NATIONAL STOCK NUMBERS (NSN) THAN WHAT IS SHOWN ON THE TITLE PAGE, PROVIDED THE BOX PACK DOES NOT VARY FROM WHAT IS DELINEATED HEREIN. THE EXPLOSIVE CLASSIFICATION OF OTHER ITEMS MAY BE DIFFERENT THAN WHAT IS SHOWN.



- STRAP BEARING PIECE, 2" X 4" X BOX WIDTH MINUS 3" (AS REQD).
NAIL TO VERTICAL PIECES W/2-101 NAILS AT EACH END. NOTE:
WHEN A UNIT HAS MORE THAN FOUR (4) BOXES OMITTED, THE
FILLER ASSEMBLY OR ASSEMBLIES LOCATED IN AN OUTER STACK ON
THE 35" SIDE OR SIDES OF THE PALLET WILL REQUIRE A "STRAP
BEARING PIECE" POSITIONED UNDER THE HORIZONTAL STRAP.
STAPLE STRAP TO THE "STRAP BEARING PIECE".

LATERAL PIECE, 2" X 4" X BOX WIDTH MINUS 3" (4 REQD). NAIL TO VERTICAL PIECES W/2-10d NAILS AT EACH END.

FILLER ASSEMBLY

(FOR MINUS ONE BOX)