APPENDIX 26J

UNITIZATION PROCEDURES FOR BOXED AMMUNITION AND COMPONENTS ON 4-WAY ENTRY PALLETS

CARTRIDGE, 40MM, PACKED 32 PER WIREBOUND BOX, UNITIZED 48 BOXES PER 35" X $45\frac{1}{2}$ " PALLET, APPROX BOX SIZE $17\frac{5}{8}$ " L X $11\frac{3}{4}$ " W X 8" H


PALLET UNIT DATA							
ITEMS INCLUDED		HAZARD CLASSIFICATION ®				WEIGHT	
NSN	DOD IC	DOT CLASS	CG CLASS	QD CLASS	COMP GROUP	(LBS)	
1310- 00-935-9229 00-935-9230	B537 B538	C C	XI-B I	1. 4 1. 4	G G	2, 236 2, 236	

NOTICE: THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002.

• HAZARD CLASSIFICATION DATA CONTAINED IN THE ABOVE CHART IS FOR GUIDANCE AND INFORMATIONAL PURPOSES ONLY. VERIFICATION OF THE SPECIFIED DATA SHOULD BE MADE BY CONSULTING THE MOST RECENT JOINT HAZARD CLASSIFICATION SYSTEM LISTING OR OTHER APPROVED LISTING(S).

REVISIONS	B.L. /2 WREheur			
	GRG/ W+Enst			
	APPROVES, U. S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND			
	and Heinton muchan			
	APPROVED BY ORDER OF COMMANDING GENERAL, U. S. ARMY MATERIEL DEVELOPMENT AND RESOURCES COMMAND (SARCOM)			
	U.S. AMEY DEFENSE AMBANTON CENTER AND SCHOOL			
	U. S. ARMY DARCOM DRAWING			
	NOVEMBER 1983			
	CLASS DIVISION DRAWING FILE			
	40 49 4116/ 20PA			
	19 48 _{26J} 1002			

DO NOT SCALE




GENERAL NOTES

- A. THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNTIZATION PROCEDURES DRAWING
 19-48-4116-20PA1002. TO PRODUCE AN APPROVED UNIT LOAD, ALL
 PERTINENT PROCEDURES, SPECIFICATIONS AND CRITERIA SET FORTH
 WITHIN THE BASIC DRAWING WILL APPLY TO THE PROCEDURES DELINEATED IN THIS APPENDIX. ANY EXCEPTIONS TO THE BASIC PROCEDURES
 ARE SPECIFIED IN THIS APPENDIX.
- B. DIMENSIONS, CUBE AND WEIGHT OF A PALLET UNIT WILL VARY SLIGHTLY DEPENDING UPON THE ACTUAL DIMENSIONS OF THE BOXES AND THE WEIGHT OF THE SPECIFIC ITEM BEING UNITIZED.
- C. INSTALL EACH HORIZONTAL STRAP TO ENCIRCLE A LAYER OF BOXES ON THE PALLET. NOTE THAT THE STRAPS WILL BE LOCATED AS DIMEN-SIONED, NEAR THE TOP OF EACH LAYER, HORIZONTAL STRAPS MUST BE TENSIONED AND SEALED PRIOR TO APPLICATION OF TIEDOWN STRAPS.
- D. INSTALL EACH TIEDOWN STRAP TO PASS UNDER THE TOP DECK BOARDS OF THE PALLET AND TO BE LOCATED AS SHOWN, TIEDOWN STRAPS WILL NOT BE APPLIED UNTIL THE HORIZONTAL STRAPS HAVE BEEN TENSIONED AND SEALED.
- E. THE FOLLOWING DARCOM DRAWINGS ARE APPLICABLE FOR OUTLOADING AND STORAGE OF THE ITEMS COVERED BY THIS APPENDIX.

CARLOADING ----- DRAWING 19-48-4115-5PA 1002
TRUCKLOADING --- DRAWING 19-48-4117-11PA 1003
STORA GE ----- DRAWING 19-48-4118-1-2-3-4-14-22PA 1002

- F. FOR METHOD OF SECURING A STRAP CUTTER TO THE PALLET UNIT, SEE DARCOM DRAWING 19-48-4127-20P1000.
- G. IF ITEMS COVERED HEREIN ARE UNITIZED PRIOR TO ISSUANCE OF THIS APPENDIX, THE BOXES NEED NOT BE REUNITIZED SOLELY TO CONFORM TO THIS APPENDIX.
- H. THE UNITIZATION PROCEDURES DEPICTED HEREIN MAY ALSO BE USED FOR UNITIZING 40MM CARTRIDGES WHEN IDENTIFIED BY DIFFERENT NATIONAL STOCK NUMBERS (NSN.) THAN WHAT IS SHOWN ON THE TITLE PAGE, PROVIDED THE BOX PACK DOES NOT VARY FROM WHAT IS DELINEATED HEREIN. THE EXPLOSIVE CLASSIFICATION OF OTHER ITEMS MAY BE DIFFERENT THAN WHAT IS SHOWN.
- J. WHEN THE UNIT LOAD DEPICTED AT LEFT IS TO BE USED FOR UNITIZING MARINE CORPS AMMUNITION, TWO LAYERS OF BOXES MUST BE OMITTED, TIEDOWN STRAP LENGTHS MUST BE DECREASED TO 12'-4", AND TWO HORIZONTAL STRAPS MUST BE OMITTED. THIS WILL RESULT IN AN OVERALL UNIT HEIGHT OF 37-1/2", A GROSS UNIT WEIGHT OF 1,513 POUNDS, AND A UNIT CUBE OF 36.0 CUBIC FEET. ADDITIONALLY, THE UNIT LOAD MAY BE MODIFIED AS DESCRIBED WHEN BEING SHIPPED BY MILVAN OR COMMERCIAL INTERMODAL FREIGHT CONTAINER, CONVENTIONAL VAN TRAILER OR CONVENTIONAL OR HIGH-CAPACITY BOXCAR. THE DETERMINATION TO REDUCE THE LOAD BY LAYER(S) FOR TRANSPORTATION WILL BE MADE BY THE RESPONSIBLE COMMAND AND WILL BE BASED UPON ECONOMICS OF TRANSPORTATION AND HANDLING.



FILLER ASSEMBLY

(FOR MINUS ONE BOX)

PAGE 2