APPENDIX 65H

UNITIZATION PROCEDURES FOR BOXED AMMUNITION AND COMPONENTS ON 4-WAY ENTRY PALLETS

HAND GRENADE, PACKED 25 PER WOODEN BOX, UNITIZED 36 BOXES PER 35" X $45\frac{1}{2}$ " PALLET; APPROX BOX SIZE $17\frac{3}{4}$ " L X $16\frac{1}{4}$ " W X $7\frac{1}{2}$ " H


		PALLE	T UNIT D	ATA		
ITEMS INCLUDED		HAZARD CLASSIFICATION ●				WEIGHT
NSN	DODIC	DOT CLASS	CG CLASS	QD CLASS	COMP GROUP	(LBS)
1330- 00-028-5832 00-028-5837 00-301-1970	G890 G890 G890	A A A	IV IV IV	(08) 1, 1 (08) 1, 1 (08) 1, 1	F F F	2, 123 2, 231 2, 231

NOTICE: THIS APPENDIX CANNOT STAND ALONE BUT MUST RE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002.

CHAZARD CLASSIFICATION DATA CONTAINED IN THE ABOVE CHART IS FOR GUIDANCE AND INFORMATIONAL PURPOSES ONLY. VERTICIATION OF THE SPECIFIED DATA SHOULD BE MADE BY CONSULTING THE MOST RECENT JOINT HAZARD CLASSIFICATION SYSTEM LISTING OR OTHER APPROVED LISTING(S).

DO NOT SCALE

REVISIONS		DRAFTSMAN	80	3/WW			
			RSH /	94	Syn J		
			APPROVED U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND MEMORY ORSAC-THO ORSAC-THO				
			APPROVED BY ORDER OF COMMANDING GENERAL, U. S. ARMY MATERIEL DEVELOPMENT AND BEADINESS COMMAND (DARCOM)				
			U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL				
			U. S. ARMY DARCOM DRAWING				
		FEBRUARY 1984					
			CLASS	DIVISION	DRAWING	FILE	
			19	48	4116/	20PA	
	/_		19	40	65H	1002	



BILL OF MATERIA	AL	
PALLET, 35" X 45-1/2" 1	REQD	 65 LBS
STEEL STRAPPING, 3/4"77.00"	REQD	5.50 LBS
SEAL FOR 3/4" STRAPPING 5	REQD	NIL


TOTAL WEIGHT -----

GENERAL NOTES

- A. THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CON-JUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002. TO PRODUCE AN APPROVED UNIT LOAD, ALL PERTINENT PROCEDURES, SPECIFICATIONS AND CRITERIA SET FORTH WITHIN THE BASIC DRAWING WILL APPLY TO THE PROCEDURES DELINEATED IN THIS APPENDIX. ANY EXCEPTIONS TO THE BASIC PROCEDURES ARE SPECIFIED IN THIS APPENDIX.
- B. DIMENSIONS, CUBE AND WEIGHT OF A PALLET UNIT WILL VARY SLIGHTLY DEPENDING UPON THE ACTUAL DIMENSIONS OF THE BOXES AND THE WEIGHT OF THE SPECIFIC ITEM BEING UNITIZED.
- C. THE LOAD STRAPS MAY BE THREADED THROUGH THE STRAP SLOTS OF A PALLET OR PRE-POSITIONED ON THE PALLET DECK PRIOR TO PLACING BOXES ON THE PALLET. LOAD STRAPS WILL BE TENSIONED AND SEALED PRIOR TO APPLICATION OF TIEDOWN STRAPS.
- D. INSTALL EACH TIEDOWN STRAP TO PASS UNDER THE TOP DECK BOARDS OF THE PALLET AND TO BE LOCATED AS SHOWN. TIEDOWN STRAPS WILL NOT BE APPLIED UNTIL THE LOAD STRAPS HAVE BEEN TENSIONED AND SEALED. NOTE: IF THE BOXES OF A PALLET UNIT DO NOT OVERHANG THE PALLET DECK SUFFICIENTLY TO ALLOW THE TIEDOWN STRAPS TO CONTACT THE BOXES IN THE BOTTOM LAYER OF THE UNIT, INSTALL EACH TIEDOWN STRAP TO ENCIRCLE THE UNIT AND BE POSITIONED ON THE END CLEATS OF THE BOXES IN EACH STACK.
- E. THE FOLLOWING DARCOM DRAWINGS ARE APPLICABLE FOR OUTLOADING AND STORAGE OF THE ITEMS COVERED BY THIS APPENDIX.

CARLOADING	DRAWING	19-48-4115-5PA1002
TRUCKLOADING	DRAWING	19-48-4117-11PA1003
STORAGE	DRAWING	19-48-4118-1-2-444-184 :

- F. FOR METHOD OF SECURING A STRAP CUTTER TO THE PALLET UNIT, SEE DARCOM DRAWING 19-48-4127-20P1000.
- G. IF ITEMS COVERED HEREIN ARE UNITIZED PRIOR TO ISSUANCE OF THIS APPENDIX, THE BOXES NEED NOT BE REUNITIZED SOLELY TO CONFORM TO THIS APPENDIX.
- H. THE UNITIZATION PROCEDURES DEPICTED HEREIN MAY ALSO BE USED FOR UNITIZING GRENADES WHEN IDENTIFIED BY DIFFERENT NATIONAL STOCK NUMBERS (NSN.) THAN WHAT IS SHOWN ON THE TITLE PAGE, PROVIDED THE BOX PACK DOES NOT VARY FROM WHAT IS DELINEATED HEREIN. THE EXPLOSIVE CLASSIFICATION OF OTHER ITEMS MAY BE DIFFERENT THAN WHAT IS SHOWN.
- J. WHEN THE UNIT LOAD DEPICTED AT LEFT IS TO BE USED FOR UNITIZING MARINE CORPS AMMUNITION, ONE LAYER OF BOXES MUST BE OMITTED, TIEDOWN STRAP LENGTHS MUST BE DECREASED TO 13'-3", AND LOAD STRAP LENGTHS MUST BE DECREASED TO 15'-6". THIS WILL RESULT IN AN OVERALL UNIT HEIGHT OF 4,7 & GROSS UNIT WEIGHT OF 1,781, POUNDS, AND A UNIT CUBE OF 43,1 CU FT. ADDITIONALLY, THE UNIT LOAD MAY BE MODIFIED AS DESCRIBED WHEN BEING SHIPPED BY MILVAN OR COMMERCIAL INTERMODAL REIGHT CONTAINER, CONVENTIONAL VAN TRAILER OR CONVENTIONAL OR HIGH-CAPACITY BOXCAR. THE DETERMINATION TO REDUCE THE LOAD BY A LAYER FOR TRANSPORTATION WILL BE MADE BY THE RESPONSIBLE COMMAND AND WILL BE BASED UPON ECONOMICS OF TRANSPORTATION AND HANDLING.



-- 2,123 LBS (APPROX)

----- 50.6 CU FT (APPROX)