## APPENDIX 95D

## UNITIZATION PROCEDURES FOR BOXED AMMUNITION AND COMPONENTS ON 4-WAY ENTRY PALLETS

MINE, ANTITANK, PACKED 2 PER WOODEN BOX, UNITIZED 36 BOXES PER 40" X 48" PALLET; APPROX BOX SIZE 16\frac{1}{4}" L X 10\frac{5}{8}" W X 16" H


PALLET UNIT DATA									
ITEMS INCLUDED		H.	WEIGHT						
NSN	DODIC	DOT CLASS	CG CLASS	QD CLASS	COMP GROUP	(LBS)			
1345- 00-324-1425 00-348-8646	K250 K250	A A	VII	1,1 1,1	D D	2,679 2,679			

NOTICE: THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CONJUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002.

● HAZARD CLASSIFICATION DATA CONTAINED IN THE ABOVE CHART IS FOR GUIDANCE AND INFORMATIONAL PURPOSES ONLY. VERIFICATION OF THE SPECIFIED DATA SHOULD BE MADE BY CONSULTING THE MOST RECENT JOINT HAZARD CLASSIFICATION SYSTEM LISTING OR OTHER APPROVED LISTING (S).

REVIS	PAPTEMAN	THER BB	4/New				
		RSH0	Sol	Byrd			
/		APPROVED, U. S. ARMY ARMAMENT, MUNITIONS AND GHEMICAL.					
		- Heith HBenton Proposed THE					
		APPROVED BY ORDER OF COMMANDING GENERAL, U. S. ARMY MATERIEL DEVELOPMENT AND READINESS COMMAND (DARCOM)					
		U.S. ARMY DEPENDE AMERICATION CENTER AND SCHOOL					
		U. S. ARMY DARCOM DRAWING					
		NOVEMBER 1983					
		CLASS	DIVISION	DRAWING	FILE		
		19	48	4116/95D	20PA		
					1002		


DO NOT SCALE





## **GENERAL NOTES**

- A. THIS APPENDIX CANNOT STAND ALONE BUT MUST BE USED IN CON-JUNCTION WITH THE BASIC UNITIZATION PROCEDURES DRAWING 19-48-4116-20PA1002. TO PRODUCE AN APPROVED UNIT LOAD, ALL PERTINENT PROCEDURES, SPECIFICATIONS AND CRITERIA SET FORTH WITHIN THE BASIC DRAWING WILL APPLY TO THE PROCEDURES DELINEATED IN THIS APPENDIX. ANY EXCEPTIONS TO THE BASIC PROCEDURES ARE SPECIFIED IN THIS APPENDIX.
- B. DIMENSIONS, CUBE AND WEIGHT OF A PALLET UNIT WILL VARY SLIGHTLY DEPENDING UPON THE ACTUAL DIMENSIONS OF THE BOXES AND THE WEIGHT OF THE SPECIFIC ITEM BEING UNITIZED.
- C. INSTALL EACH HORIZONTAL STRAP TO ENCIRCLE A LAYER OF BOXES ON THE PALLET. HORIZONTAL STRAPS MUST BE TENSIONED AND SEALED PRIOR TO APPLICATION OF TIEDOWN STRAPS.
- D. INSTALL EACH TIEDOWN STRAP TO PASS UNDER THE TOP DECK BOARDS OF THE PALLET AND TO BE LOCATED AS SHOWN. TIEDOWN STRAPS WILL NOT BE APPLIED UNTIL THE HORIZONTAL STRAPS HAVE BEEN TENSIONED AND SEALED.
- E. THE FOLLOWING DARCOM DRAWINGS ARE APPLICABLE FOR OUTLOADING AND STORAGE OF THE ITEMS COVERED BY THIS APPENDIX.

- F. FOR METHOD OF SECURING A STRAP CUTTER TO THE PALLET UNIT, SEE DARCOM DRAWING 19-48-4127-20P1000.
- G. IF ITEMS COVERED HEREIN ARE UNITIZED PRIOR TO ISSUANCE OF THIS APPENDIX, THE BOXES NEED NOT BE REUNITIZED SOLELY TO CONFORM TO THIS APPENDIX.
- H. THE UNITIZATION PROCEDURES DEPICTED HEREIN MAY ALSO BE USED FOR UNITIZING ANTITANK MINES WHEN IDENTIFIED BY DIFFERENT NATIONAL STOCK NUMBERS (NSN) THAN WHAT IS SHOWN ON THE TITLE PAGE, PROVIDED THE BOX PACK DOES NOT VARY FROM WHAT IS DELINEATED HEREIN. THE EXPLOSIVE CLASSIFICATION OF OTHER ITEMS MAY BE DIFFERENT THAN WHAT IS SHOWN.
- J. WHEN THE UNIT LOAD DEPICTED AT LEFT IS TO BE USED FOR UNITIZING MARINE CORPS AMMUNITION, I LAYER OF BOXES MUST BE OMITTED, TIEDOWN STRAP LENGTHS MUST BE DELETED. THIS WILL RESULT IN AN OVER HORIZGINEAL STRAP MLST BE DELETED. THIS WILL RESULT IN AN OVERALL UNIT HEIGHT OF 37-1/2", A GROSS UNIT WEIGHT OF 1,814 LBS, AND A UNIT CUBE OF 45,0 CU FT. ADDITIONALLY, THE UNIT LOAD MAY BE MODIFIED AS DESCRIBED WHEN BEING SHIPPED BY MILVAN OR COMMERCIAL INTERMODAL PREIGHT CONTAINER, CONVENTIONAL VAN TRAILER OR CONVENTIONAL OR HIGH-CAPACITY BOXCAR. THE DETERMINATION TO REDUCE THE LOAD BY A LAYER FOR TRANSPORTATION WILL BE MADE BY THE RESPONSIBLE COMMAND AND WILL BE BASED UPON ECONOMICS OF TRANSPORTATION AND HANDLING.







STRAP BEARING PIECE, 2" X 4" X BOX WIDTH MINUS 3" (AS REQD), NAIL TO VERTICAL PIECES W/2-10d NAILS AT EACH END. MOTE: WHEN A UNIT HAS MORE THAN SX (6) BOXES OMITTED, THE FILLER ASSEMBLY OR ASSEMBLES LOCATED IN AN OUTER STACK ON THE 40" SIDE OF THE PALLET WILL REQUIRE A "STRAP BEARING PIECE" POSITIONED UNDER THE HORIZONTAL STRAP, STAPLE STRAP TO THE "STRAP BEARING PIECE".

LATERAL PIECE, 2" X 4" X BOX WIDTH MINUS 3" (4 REQD), NAIL TO VERTICAL PIECES W/2-10d NAILS AT EACH END.

## FILLER ASSEMBLY

( FOR MINUS ONE BOX )