
STORAGE IN 60' & 80' IGLOO AND 80' STRADLEY MAGAZINES OF 750-POUND BOMB (HIGH EXPLOSIVE) PACKED TWO PER WOODEN PALLET


INDEX

	PAGE(S)
GENERAL NOTES, AND MATERIAL SPECIFICATIONS	3
IGLOO STORAGE PROCEDURES	2,3
STRADLEY STORAGE PROCEDURES	4,5
DETAILS	

CHECKER BY HOLE CHECKER BY WE HAVE APSA C. 7.1.	CHARL GL, Cirk C. COMMANDING OFFICER. SAVANNA ARRY DEPOT
REVISIONS	Sy. 10. Cic. relation
	APPROVED BY GRIDER OF CORRESPOND SERVICE U. S. ARRY MATCHEL, CORRAND Paul Change
	U. S. ARMY MATERIEL COMMAND
	CLASS DIVISION DRAWING FILE
	19 48 4094 I-I4PB
	1001

O NOT SCALE





BILL OF	MATERIAL (PER	40-UNII STACK
LUMBER	LINEAR FEET	BOARD FEET
1" X 2"	54	9
1" X 4"	240	80
3" X 4"	100	.100
NAILS	NO. REQD	POUNDS
4d (1-1/2")	128	1/2
12d (3-1/4°)	128	2-1/4
WEDGES	NO. REQD	
2" X 4" X 9'-0"	4	

MATERIAL SPECIFICATIONS

LUMBER: SEE TM 743-200-1, DUNNAGE LUMBER; FED SPEC MM-L-751.


NAILS -: COMMON, CEMENT COATED OR CHEMICALLY ETCHED, FED SPEC FF-N-105.
ALT: ANNULAR-RING TYPE NAIL OF SAME SIZE.


c.	AISLE DIMENSIONS SHOWN HEREIN MAY BE ADJUSTED TO SUIT LOCAL CONDITIONS AND/OR AVAILABLE MATERIALS HANDLING EQUIPMENT (MHE). HOWEVER, FOR USE OF THE TPO 1325-926-1868 PALLET, A NINETEEN INCH (19") (MINIMUM) LATERAL INSPECTION AISLE IS REQUIRED; FOR USE OF THE TPO 1325-SPCT-06003 PALLET, A TWENTY-THREE INCH (23") (MINIMUM) LATERAL INSPECTION AISLE IS REQUIRED TO FACILITATE INSPECTION OF BOMBS AT BOTH ENDS.
	BOMBS AT BOTH ENDS.

- D. IF THE AVAILABLE MATERIALS HANDLING EQUIPMENT (MHE) PERMITS, ADDITIONAL PALLET UNITS MAY BE STORED WITHIN THE FRONTAL AREA OF THE MAGAZINES.
- E. STORED PALLET UNITS MUST NOT CONTACT THE WALL OF A MAGAZINE. TO PROVIDE FOR THIS MANDATORY CLEARANCE REQUIREMENT, PALLET UNITS MAY BE ELIMINATED FROM THE DEPICTED STACKING PATTERN AS NECESSARY, OR AISLE DIMENSIONS MAY BE ADJUSTED AS PER GENERAL NOTE "C", ABOVE.
- F. CARE SHOULD BE EXERCISED WHEN STORING, SO THAT THE EX-PLOSIVE LIMIT FOR THE MAGAZINE IS NOT EXCEEDED.
- G. STORAGE AS SHOWN DEPICTS USE OF PALLET UNIT SPECIFIED BY TPO 1325-926-1868. THE STORAGE METHODS SHOWN ARE ALSO APPLICABLE TO THE STORAGE METHODS SHOWN ARE ALSO TPO 1325-SPCT-06003. NOTICE: WHEN STORING PALLET UNITS AS SPECIFIED BY TPO 1325-SPCT-06003, THE "STACK STABILIZING ASSEMBLY" METHOD OF DUNINAGING STACKS WILL NOT BE USED. HOWEVER, WEDGES WILL BE REQUIRED AS SPECIFIED HEREIN.
- CAUTION: PALLET UNITS WILL NOT BE STACKED MORE THAN THREE (3) HIGH WITHOUT STAGGER-STACKING THE UPPER LAYERS AS SHOWN.

IGLOO STORAGE PROCEDURES

PAGE 3






PALLET UNIT ------ 504 BOMB ----- 1,008 EXPLOSIVE WEIGHT ---- 389,000 LBS (APPROX)

- INDICATES DIRECTION OF BOMB NOSE.

FOR "GENERAL NOTES" AND
"MATERIAL SPECIFICATIONS", SEE PAGE 3


ISOMETRIC VIEW (80' STRADLEY MAGAZINE)





BILL OF MATERIAL (PER 42-UNIT STACK)					
LUMBER	LINEAR FEET	BOARD FEET			
1" × 2"	57	10			
1" X 4".	255	85			
3" X 4"	105	105			
NAILS	NO. REQD	POUNDS			
4d (1-1/2")	136	1/2			
12d (3-1/4")	136	2-1/2			
WEDGES	NO. REQD				
2" X 4" X 9'-0"		4			


STRADLEY STORAGE PROCEDURES

PAGE 5









STACK STABILIZING ASSEMBLY

ASSEMBLY IS ONLY TO BE USED WITH
TPO 1325-926-1868 PALLET UNIT. (1. REQD
WITH EACH PALLET STORED ABOVE FLOOR
LEVEL). NOTE THAT IF 3" x 4" MATERIAL
IS NOT AVAILABLE, THE "UPPER PIECE" CAN
BE MADE BY LAMINATING MATERIAL OF
OTHER THICKNESSES, SUCH AS PROVIDED BY
2" X 4" AND 1" X 4" PIECES.