

APPROVED BY
BUREAU OF EXPLOSIVES

dan healy Digitally signed by dan healy
DN: cn=dan healy, o, ou,
email=dan_healy@aar.com,
c=US
Date: 2011.06.23 12:05:22 -05'00'

PATRIOT

LOADING AND BRACING* ON COM- MERCIAL FLATRACK ISO CONTAIN- ERS OF PATRIOT (PAC-3) PACKED IN SHIPPING AND STORAGE CANISTERS

INDEX

| <u>ITEM</u> | <u>PAGE(S)</u> |
|---|----------------|
| GENERAL NOTES AND MATERIAL SPECIFICATIONS | 2 |
| CANISTER DETAILS | 3 |
| TYPICAL LOADING PROCEDURES | 4-5 |
| DETAILS | 6-7 |

DISTRIBUTION STATEMENT A:

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION IS UNLIMITED.

® THE PROCEDURES SHOWN HEREIN ARE APPLICABLE TO LOADS THAT ARE TO
BE SHIPPED BY TRAILER/CONTAINER-ON- FLATCAR (T/COFC) RAIL, MOTOR, OR
WATER CARRIERS.

U.S. ARMY MATERIEL COMMAND DRAWING

| | | | | | | | | |
|---|-----------------------|---|--|-------------------------|--------------|-----------------|----------------|----------------|
| <p>APPROVED, U.S. ARMY AVIATION AND MISSILE COMMAND</p> <p>SCHMITT.ELIZABETH.1016576081 ETH.1016576081</p> <small>Digitally signed by SCHMITT.ELIZABETH.1016576081 DN: c=US, ou=U.S. Government, ou=DoD, ou=PKI, ou=USA, cn=SCHMITT.ELIZABETH.1016576081 Reason: I am approving this document Date: 2011.07.07 10:18:51 -05'00'</small> | | <p>CAUTION: VERIFY PRIOR TO USE AT WWW.DAC.ARMY.MIL THAT THIS IS THE MOST CURRENT VERSION OF THIS DOCUMENT. THIS IS PAGE 1 OF 8.</p> | | | | | | |
| | | <p>DO NOT SCALE</p> | | <p>JULY 2011</p> | | | | |
| <p>ENGINEER OR TECHNICIAN</p> | <p>BASIC REV.</p> | <p>RICHARD GARSIDE</p> | | | | | | |
| <p>APPROVED BY ORDER OF COMMANDING GENERAL, U.S. ARMY MATERIEL COMMAND</p> <p>CARNEY.GARY.BURTON.1038708038 RTON.1038708038</p> <small>Digitally signed by CARNEY.GARY.BURTON.1038708038 DN: c=US, ou=U.S. Government, ou=DoD, ou=PKI, ou=USA, cn=CARNEY.GARY.BURTON.1038708038 Date: 2011.08.15 07:46:37 -05'00'</small> | | <p>TRANSPORTATION ENGINEERING DIVISION</p> | <p>FIEFFER.LAUR A.A.1230375727</p> <small>Digitally signed by FIEFFER.LAURA.A.1230375727 DN: c=US, ou=U.S. Government, ou=DoD, ou=PKI, ou=USA, cn=FIEFFER.LAURA.A.1230375727 Date: 2011.08.17 15:10:50 -05'00'</small> | <p>TESTED</p> | <p>CLASS</p> | <p>DIVISION</p> | <p>DRAWING</p> | <p>FILE</p> |
| <p>U.S. ARMY DEFENSE AMMUNITION CENTER</p> | | <p>VALIDATION ENGINEERING DIVISION</p> | <p>BARICKMAN. PHILIP.W.123 0202202</p> <small>Digitally signed by BARICKMAN.PHILIP.W.123020202 DN: c=US, ou=U.S. Government, ou=DoD, ou=PKI, ou=USA, cn=BARICKMAN.PHILIP.W.123020202 Date: 2011.06.20 14:06:22 -05'00'</small> | | <p>19</p> | <p>48</p> | <p>8222</p> | <p>GM15PA6</p> |
| | | <p>ENGINEERING DIRECTORATE</p> | <p>BEAVER.JERRY W.1230949952</p> <small>Digitally signed by BEAVER.JERRY.W.1230949952 DN: c=US, ou=U.S. Government, ou=DoD, ou=PKI, ou=USA, cn=BEAVER.JERRY.W.1230949952 Date: 2011.06.20 16:26:06 -05'00'</small> | | | | | |

GENERAL NOTES

- A. THIS DOCUMENT HAS BEEN PREPARED AND ISSUED IN ACCORDANCE WITH AR 740-1 AND AUGMENTS TM 743-200-1 (CHAPTER 5).
- B. ALL LOADS SHIPPED BY THE PROCEDURES DEPICTED IN THIS DRAWING MUST BE IN ACCORDANCE WITH THE REQUIREMENTS SET FORTH IN TITLE 49, THE UNITED STATES CODE OF FEDERAL REGULATIONS; AR 55-355/AFM 75-2; DOD 4500.32-R; DOD 5100.76-M; DOD 6055.9-STD; AS WELL AS ANY AND ALL OTHER APPLICABLE SERVICE REGULATIONS.
- C. THE SPECIFIED OUTLOADING PROCEDURES ARE APPLICABLE TO LOADS OF PATRIOT ADVANCED CAPABILITY-3 (PAC-3) COMPLETE ROUND, WHEN PACKED IN THE MISSILE CANISTER (SHIPPING, STORAGE AND LAUNCH CANISTER). SEE PAGE 3 AND LOCKHEED-MARTIN DRAWING 13506000 FOR DETAILS OF THE CANISTERS. **CAUTION:** REGARDLESS OF THE QUANTITY OF CANISTERS TO BE SHIPPED, THE "MAXIMUM GROSS WEIGHT" OF THE FLATRACK ISO CONTAINER MUST NOT BE EXCEEDED.
- D. THE LOAD AS SHOWN IS BASED ON A 5,700 POUND 20' LONG BY 8' WIDE FLATRACK ISO CONTAINER WITH FULL HEIGHT ENDWALLS, AND INSIDE DIMENSIONS OF 19'-4" LONG BY 7'-2" WIDE. THE LOAD IS DESIGNED FOR TRAILER/CONTAINER-ON-FLATCAR (T/COFC) SHIPMENT, HOWEVER, THE LOAD AS DESIGNED CAN ALSO BE MOVED BY OTHER SURFACE MODES OF TRANSPORT. **NOTICE:** OTHER CONTAINERS OF THE SAME DESIGN CONFIGURATION CAN BE USED.
- E. WHEN LOADING CANISTERS, THEY ARE TO BE POSITIONED SO AS TO ACHIEVE A TIGHT LOAD BETWEEN THE END BLOCKING ASSEMBLY AND THE LADING. ALTHOUGH A TOTAL OF 1" OF UNBLOCKED SPACE ACROSS THE WIDTH OF A LOAD IS PERMITTED, LONGITUDINAL VOIDS WITHIN THE LOAD ARE TO BE HELD TO A MINIMUM, NOT EXCEEDING 1/2". EXCESSIVE SLACK CAN BE ELIMINATED FROM A LOAD BY LAMINATING ADDITIONAL PIECES OF APPROPRIATE THICKNESS TO THE FILLER ASSEMBLIES OF THE END BLOCKING ASSEMBLY.
- F. DUNNAGE LUMBER SPECIFIED IS OF NOMINAL SIZE. FOR EXAMPLE, 1" X 4" MATERIAL IS ACTUALLY 3/4" THICK BY 3-1/2" WIDE AND 2" X 6" MATERIAL IS ACTUALLY 1-1/2" THICK BY 5-1/2" WIDE.
- G. A STAGGERED NAILING PATTERN WILL BE USED WHENEVER POSSIBLE WHEN NAILS ARE DRIVEN INTO JOINTS OF DUNNAGE ASSEMBLIES OR WHEN LAMINATING DUNNAGE. ADDITIONALLY, THE NAILING PATTERN FOR AN UPPER PIECE OF LAMINATED DUNNAGE WILL BE ADJUSTED AS REQUIRED SO THAT A NAIL FOR THAT PIECE WILL NOT BE DRIVEN THROUGH ONTO OR RIGHT BESIDE A NAIL IN A LOWER PIECE.
- H. WHEN INSTALLING END BLOCKING ASSEMBLIES, THE ASSEMBLIES MUST BE POSITIONED SO AS TO BE SUPPORTED AND IN LINE WITH THE STRONG POINTS OF THE FLATRACK ENDWALLS.
- J. WHEN STEEL STRAPPING IS SEALED IN AN END-OVER-END LAP JOINT, A MINIMUM OF ONE SEAL WITH TWO PAIR OF NOTCHES WILL BE USED TO SEAL THE JOINT WHEN A NOTCH-TYPE SEALER IS BEING USED. A MINIMUM OF TWO SEALS, BUTTED TOGETHER WITH TWO PAIR OF CRIMPS PER SEAL, WILL BE USED TO SEAL THE JOINT WHEN A CRIMP-TYPE SEALER IS BEING USED. REFER TO THE "STRAP JOINT A" AND "STRAP JOINT B" DETAILS ON PAGE 8 FOR GUIDANCE.
- K. THE 2" STRAPPING USED FOR LOAD SECUREMENT, I.E., HOLD-DOWN STRAPS, WILL ONLY BE FASTENED TO THE FLATRACK CONTAINER BY UTILIZING TIE-DOWN PROVISIONS LOCATED ON THE TOP OR ALONG THE SIDE OF THE FLATRACK BOTTOM SIDE RAILS. **CAUTION:** THE LOAD SECUREMENT STRAPS WILL NOT BE POSITIONED AROUND THE UNDERSIDE OR THROUGH THE FORKLIFT POCKETS OF THE FLATRACK CONTAINER. ADDITIONALLY, THE FLATRACK TIEDOWN PROVISIONS MUST BE AT LEAST AS STRONG AS THE 2" LOAD SECUREMENT STRAPPING BEING USED; AND BE OF A SUFFICIENT WIDTH TO RECEIVE THE 2" STRAPPING AND BE OF A DESIGN WHICH WILL PROVIDE A BEARING SURFACE ACROSS THE FULL WIDTH OF THE 2" STRAPPING SO THAT THE STRAPPING WILL NOT BE DEFORMED, ESPECIALLY AT ITS EDGES, WHEN PROPERLY TENSIONED.
- L. REFER TO ASSOCIATION OF AMERICAN RAILROADS MANUAL "GENERAL RULES GOVERNING THE LOADING OF COMMODITIES ON OPEN TOP CARS" FOR APPLICABLE LOADING RULES AS FOLLOWS: PREFACE, 1, 2, 3, 5, 7, 10, 12, 13, 14, AND 15. NOTE THAT ALL STRAPPING USED FOR LOAD SECUREMENT, I.E., HOLD-DOWN STRAPS, MUST BE MARKED AS SPECIFIED IN LOADING RULE 15.
- M. WHETHER A CONTAINER IS FULL OR IS LOADED WITH A REDUCED QUANTITY OF LADING UNITS, THE LENGTHWISE CENTER OF GRAVITY OF THE LOAD MUST BE WITHIN 12", IN EITHER DIRECTION, OF THE MID-POINT OF THE CONTAINER.


(CONTINUED AT RIGHT)

(GENERAL NOTES CONTINUED)

- N. PORTIONS OF THE FLATRACK DEPICTED WITHIN THIS DRAWING, SUCH AS THE ENDWALL, HAVE NOT BEEN SHOWN IN THE LOAD VIEWS FOR CLARITY PURPOSES.
- O. **MAXIMUM LOAD WEIGHT CRITERIA:**
THE MAXIMUM LOAD WEIGHTS ARE CONTROLLED BY EQUIPMENT CAPABILITY FACTORS. ALTHOUGH THE HEAVIEST MAXIMUM LOAD IS DELINEATED IN THE LOAD VIEW, PROVISIONS ARE INCLUDED WITHIN THIS DRAWING SO THAT THE BASIC LOAD CAN BE ADJUSTED TO SATISFY A LESSER QUANTITY OF LADING UNITS. DEPENDING ON TRANSPORTATION ROUTING, IT MAY BE NECESSARY TO REDUCE THE LOAD WEIGHT TO SATISFY "WEIGHT LAWS" OF CERTAIN STATES. ALSO, IT MAY BE NECESSARY TO REDUCE THE LOAD WEIGHT TO SATISFY OTHER WEIGHT RESTRICTIONS IMPOSED ON THE INTERMODAL CONTAINER SYSTEM.
- P. REQUIREMENTS CITED WITHIN THE ASSOCIATION OF AMERICAN RAILROADS (AAR) INTERMODAL LOADING GUIDE APPLY WHEN THE SHIPMENT MOVES BY TRAILER/CONTAINER-ON-FLATCAR (T/COFC). SPECIAL T/COFC NOTES FOLLOW:
1. A LOADED CONTAINER MUST BE ON A CHASSIS EQUIPPED WITH TWO BOGIE ASSEMBLIES WHEN BEING MOVED IN TOFC SERVICE.
2. THE LOAD LIMIT OF A T/COFC RAILCAR MUST NOT BE EXCEEDED. NOR WILL A CAR BE LOADED SO THAT THE TRUCK UNDER ONE END OF THE CAR CARRIES MORE THAN ONE-HALF OF THE LOAD LIMIT FOR THAT CAR.
- Q. DURING INTRASTATE AND/OR INTERSTATE MOVES BY MOTOR CARRIER, A PROPER CHASSIS OR MODIFIED FLATBED TRAILER MUST BE USED TO PRECLUDE VIOLATION OF ONE OR MORE "WEIGHT LAWS" APPLICABLE TO THE STATE OR STATES INVOLVED.
- R. THE LOAD AS SHOWN ON PAGE 4 MAY BE REDUCED BY ONE LAYER FOR A SHIPMENT OF TWO CONTAINERS, IF DESIRED.
- S. ANTI-CHAFING MATERIAL MAY BE INSTALLED AT POINTS OF CONTACT BETWEEN CANISTERS AND BETWEEN CANISTERS AND STEEL STRAPPING, IF DESIRED, TO PREVENT CHAFING DAMAGE TO CANISTER PAINT AND MARKINGS.
- T. CONVERSION TO METRIC EQUIVALENTS: DIMENSIONS WITHIN THIS DOCUMENT ARE EXPRESSED IN INCHES AND WEIGHTS ARE EXPRESSED IN POUNDS. WHEN NECESSARY, THE METRIC EQUIVALENTS MAY BE COMPUTED ON THE BASIS OF ONE INCH EQUALS 25.4MM AND ONE POUND EQUALS 0.454 KG.
- U. RECOMMENDED SEQUENTIAL LOADING PROCEDURES FOR THE LOAD ON PAGE 4:
1. PREFABRICATE AND INSTALL TWO END BLOCKING ASSEMBLIES, STRAPPED TO ENDWALLS. SEE NOTE ON PAGE 6.
2. INSTALL TWO STACKS OF CANISTERS, EACH STACK LOADED FROM OPPOSITE SIDES OF THE FLATRACK.
3. INSTALL THE FILLER ASSEMBLIES ON THE ENDS OF THE BEAM ASSEMBLIES OF THE END BLOCKING ASSEMBLIES.
4. PREFABRICATE AND INSTALL STRAPPING ASSEMBLY AND INSTALL THE FOUR HOLD-DOWN STRAPS.
5. INSTALL EIGHT STAKES AND FOUR SIDE BLOCKING.

MATERIAL SPECIFICATIONS

- LUMBER - - - - - : SEE TM 743-200-1 (DUNNAGE LUMBER) AND VOLUNTARY PRODUCT STANDARD PS 20.
- NAILS - - - - - : ASTM F1667; COMMON STEEL NAIL (NLCMS OR NLCMMS).
- PLYWOOD - - - - - : COMMERCIAL ITEM DESCRIPTION A-A-55057, INDUSTRIAL PLYWOOD, INTERIOR WITH EXTERIOR GLUE, GRADE C-D. IF SPECIFIED GRADE IS NOT AVAILABLE, A BETTER INTERIOR OR AN EXTERIOR GRADE MAY BE SUBSTITUTED.
- STRAPPING, STEEL - - : ASTM D3953: FLAT STRAPPING, TYPE 1, HEAVY DUTY, FINISH A, B (GRADE 2), OR C.
- SEAL, STRAP - - - - : ASTM D3953: CLASS H, FINISH A, B (GRADE 2), OR C, DOUBLE NOTCH TYPE, STYLE I, II, OR IV.
- STAPLE, STRAP - - - : COMMERCIAL GRADE.
- ANTI-CHAFING MATERIAL - - - - : MIL-PRF-121 (OR EQUAL); NEUTRAL BARRIER MATERIAL.



PATRIOT (PAC-3) DETAIL


GROSS WEIGHT - - - - - 4,399 LBS (APPROX)
 CUBE - - - - - 210.2 CU FT (APPROX)

UNITIZATION AND HANDLING PROCEDURAL GUIDANCE

(PROCEDURAL GUIDANCE CONTINUED)

1. STACKING CANISTER FOR UNITIZATION.
 - A. THE UPPER CANISTER STACK FRAME MUST BE FULLY SEATED UPON THE LOCATOR PINS OF THE LOWER CANISTER.
 - B. POSITION THE FORWARD END OF THE UPPER CANISTER ABOVE THE FORWARD END OF THE LOWER CANISTER.
 - C. CANISTER INTERLOCKING BOLTS MUST BE TIGHTENED AS SECURELY AS POSSIBLE WITH A NORMAL HAND TOOL WRENCH (REF: 60 FOOT POUNDS).
2. CANISTER OR CANISTER STACK HANDLING.
 - A. ONLY APPROVED AND APPROPRIATELY SIZED MATERIAL HANDLING EQUIPMENT WILL BE USED FOR HANDLING THE DEPICTED CANISTERS. APPROVED MATERIAL HANDLING EQUIPMENT (FORKLIFT TRUCKS, CRANES, HAND TRUCKS, DOLLIES, ROLLER ASSEMBLIES, SLINGS, SPREADER BARS, ETC.) IS SPECIFIED ELSEWHERE.
 - B. IF HANDLING IS ACCOMPLISHED WITH A FORK TRUCK, THE CANISTERS SHOULD BE HANDLED FROM A SIDE POSITION AS MUCH AS POSSIBLE. CARE MUST BE EXERCISED WHEN INSERTING FORKS UNDER A CANISTER, TO PREVENT DAMAGE TO THE CANISTER BY THE FORKLIFT TINES OR THE FORKLIFT PACKAGE GUARD. FOR VERY SHORT "INCHING" SPEED MOVEMENTS, SUCH AS WILL BE EXPERIENCED DURING CONTAINER LOADING, A TWO-HIGH CANISTER STACK MAY BE HANDLED BY INSERTING THE FORKS OF THE FORKLIFT TRUCK INTO THE FORK RECEPTACLES OF THE UPPER CANISTER.
 - C. SLINGING OF A CANISTER OR A CANISTER STACK WILL BE IN ACCORDANCE WITH APPROVED PROCEDURES.
 - D. PRECAUTIONARY HANDLING TECHNIQUES NORMALLY EMPLOYED OR AS SPECIFIED FOR THE TYPE OF COMMODITY INVOLVED WILL BE OBSERVED.

(CONTINUED AT RIGHT)



ISOMETRIC VIEW

KEY NUMBERS

- ① END BLOCKING ASSEMBLY (2 REQD). SEE THE DETAIL ON PAGE 6.
- ② END BLOCKING ASSEMBLY STRAP, 1-1/4" X .031" OR .035" OR .029" X 17'-4" (4 REQD, 2 PER END BLOCKING ASSEMBLY). INSTALL EACH STRAP AROUND THE PLYWOOD, BETWEEN THE BEAMS, OF EACH END BLOCKING ASSEMBLY, AND AROUND ENDWALL.
- ③ SEAL FOR 1-1/4" STRAPPING (4 REQD, 1 PER STRAP). CRIMP EACH SEAL WITH TWO PAIR OF NOTCHES.
- ④ SIDE BLOCKING, 2" X 6" X 8'-0" AND 1" X 6" X 8'-0" (4 REQD). LAMINATE 1" X 6" PIECE TO 2" X 6" PIECE W/1-6d NAIL EVERY 6". POSITION WITH END AGAINST ENDWALL AS SHOWN
- ⑤ STAKE, 4" X 4" X 18" (8 REQD). INSTALL THE STAKE INTO THE FLATRACK STAKE POCKET WITH A TIGHT (SNUG) FIT. **NOTE:** REFERENCE DIMENSIONS FOR A TIGHT FITTING STAKE ARE 3-1/4" (ACTUAL) X 3-1/4" (ACTUAL). NAIL 1-20d NAIL THROUGH THE HOLE PROVIDED IN THE FACE OF THE FLATRACK STAKE POCKET AND INTO THE STAKE. BEND THE PROTRUDING HEAD OF THE NAIL OVER AND AGAINST THE STAKE POCKET. TOENAIL EACH STAKE TO THE SIDE BLOCKING W/2-12d NAILS.
- ⑥ STRAPPING ASSEMBLY (1 REQD). SEE THE DETAIL ON PAGE 6.
- ⑦ HOLD-DOWN STRAP, 2" X .050" OR .044" X 22'-0" LONG STEEL STRAPPING (4 REQD). INSTALL EACH STRAP FROM TWO PIECES, EACH 11'-0" LONG. FASTEN TO TIEDOWN PROVISION ON THE SIDE OF THE FLATRACK AND BRING UP TO THE TOP OF THE LOAD OVER THE STRAPPING ASSEMBLY, WHERE THEY CAN BE TENSIONED AND SEALED. STAPLE TO STRAPPING ASSEMBLY.
- ⑧ SEAL FOR 2" STRAPPING (20 REQD, 5 PER STRAP). FASTEN 2" HOLD DOWN STRAP WITH ONE SEAL AT EACH LOCATION CRIMPED WITH TWO PAIR OF NOTCHES. FASTEN PAD WITH ONE SEAL CRIMPED WITH ONE PAIR OF NOTCHES. SEE THE "TIEDOWN DETAIL" ON PAGE 7.


SPECIAL NOTES:

1. POSITION THE STRAPPING ASSEMBLY AND THE HOLD-DOWN STRAPS SO AS TO BE VERTICALLY IN LINE WITH THE FLATRACK TIEDOWN POINTS.
2. THE LOAD AS SHOWN MAY BE REDUCED BY ONE LAYER, IF DESIRED, FOR A SHIPMENT OF TWO CANISTERS.


| BILL OF MATERIAL | | |
|---|-------------|------------|
| LUMBER | LINEAR FEET | BOARD FEET |
| 1" x 6" | 32 | 16 |
| 2" x 4" | 48 | 32 |
| 2" x 6" | 92 | 92 |
| 2" x 8" | 35 | 46 |
| 4" x 4" | 12 | 16 |
| NAI LS | NO. | REQD |
| 6d (2") | 236 | 1-1/2 |
| 10d (3") | 240 | 3-3/4 |
| 12d (3-1/4") | 16 | 1/4 |
| STEEL STRAPPING, 1-1/4" - 69.3' REQD - 9.90 LBS | | |
| SEAL FOR 1-1/4" STRAPPING - - 4 REQD - 0.18 LBS | | |
| STEEL STRAPPING, 2" - - - - 88' REQD - 29.33 LBS | | |
| SEAL FOR 2" STRAPPING - - - 12 REQD - 2.40 LBS | | |
| PLYWOOD, 1/2" - - - - 59.7 SQ FT REQD - 82.14 LBS | | |
| STAPLE, 2" - - - - - - 16 REQD - 0.23 LBS | | |
| ANTI-CHAFING MATERIAL - - - AS REQD - - - - NI L | | |

LOAD AS SHOWN

| ITEM | QUANTITY | WEIGHT (APPROX) |
|---------------------------------|----------|---------------------|
| CANISTER - - - - - 4 - - - - - | | 17,596 LBS |
| DUNNAGE - - - - - - - - - - - | | 533 LBS |
| CONTAINER - - - - - - - - - - - | | 4,700 LBS |
| TOTAL WEIGHT - - - - - | | 22,829 LBS (APPROX) |




STRAPPING ASSEMBLY



END BLOCKING ASSEMBLY

NOTE: FOR A ONE HIGH LOAD, ELIMINATE THE TOP TWO PLYWOOD PIECES, THE TOP TWO BEAMS, AND THE TOP NINE FILLER PIECES, AND SHORTEN THE VERTICAL PIECES TO 34".



TIEDOWN DETAIL

NOTE: THIS PROCEDURE IS USED FOR TIEDOWN OF LOAD USING FLATRACK SIDE RAIL TIEDOWN POINTS.

PARTIAL SIDE VIEW



ONE SEAL WITH TWO PAIR OF NOTCHES.

STRAP JOINT A

METHOD OF SECURING A STRAP JOINT WHEN USING A NOTCH-TYPE SEALER.



TWO SEALS, BUTTED TOGETHER, WITH TWO PAIR OF CRIMPS EACH SEAL.

STRAP JOINT B

METHOD OF SECURING A STRAP JOINT WHEN USING A CRIMP-TYPE SEALER.

